



RATINGS AND FUEL CONSUMPTION

	mhp	bhp	bkW	rpm	U.S. g/h	g/bkW-hr	EPA -	IMO -	EU
A	715	705	526	1200	35.9	216.8	NC -	NC -	NC
A	867	855	637	1600	41.6	207.1	NC -	NC -	NC
A	867	855	637	1800	43.5	216.8	NC -	NC -	NC
B	816	805	600	1300	41.3	218.5	NC -	NC -	NC
B	918	905	675	1600	43.8	206.2	NC -	NC -	NC
B	973	960	716	1800	48.6	215.7	NC -	NC -	NC
C	831	820	611	1300	42.1	218.4	NC -	NC -	NC
C	1014	1000	746	1800	50.6	215.5	NC -	NC -	NC
D	1166	1150	857	1800	58.7	217.4	NC -	NC -	NC

	LE	H	WE
min.	81.8 in/2077 mm	71.0 in/1803 mm	67.1 in/1703 mm
max.	81.8 in/2077 mm	71.0 in/1803 mm	67.1 in/1703 mm

Vee 8, 4-Stroke-Cycle Diesel

Aspiration	TTA	
Bore x Stroke	6.7 x 7.5 in	170 x 190 mm
Displacement	2105 cu in	34.5 liter
Rotation (from flywheel end)	Counterclockwise or clockwise	
Engine dry weight (approx)	11,499 lb	5216 kg