



### RATINGS AND FUEL CONSUMPTION

Generator Set							
	ekW @ .8pf	kVA	rpm	U.S. g/h	g/bkW-hr	EPA-IMO -	EU
<b>60 Hertz</b>	42.0R <sup>1</sup>	53.0	1800	3.4	235.2	T2C-NST-	NC
<b>60 Hertz</b>	44.0 <sup>1</sup>	55.0	1800	3.4	224.5	T2C-NST-	NC
<b>60 Hertz</b>	56.0R <sup>1</sup>	70.0	1800	4.5	233.5	T2C-NST-	NC
<b>60 Hertz</b>	58.5 <sup>1</sup>	73.0	1800	4.2	208.6	T2C-NST-	NC
<b>60 Hertz</b>	72.0R <sup>1</sup>	90.0	1800	5.8	234.0	T2C-NST-	NC
<b>60 Hertz</b>	76.0 <sup>1</sup>	95.0	1800	5.8	221.7	T2C-NST-	NC
<b>60 Hertz</b>	95.0R <sup>1</sup>	119.0	1800	7.3	223.3	T2C-NST-	NC
<b>60 Hertz</b>	99.0 <sup>1</sup>	123.0	1800	7.3	214.2	T2C-NST-	NC
<b>50 Hertz</b>	36.0R <sup>1</sup>	45.0	1500	2.9	234.0	NC-NST-CCNR2	
<b>50 Hertz</b>	38.0 <sup>1</sup>	47.5	1500	2.9	221.7	NC-NST-CCNR2	
<b>50 Hertz</b>	49.0R <sup>1</sup>	61.0	1500	3.9	231.2	NC-NST-CCNR2	
<b>50 Hertz</b>	51.5 <sup>1</sup>	64.5	1500	3.9	220.0	NC-NST-CCNR2	
<b>50 Hertz</b>	65.0R <sup>1</sup>	81.0	1500	4.9	219.0	NC-NST-CCNR2	
<b>50 Hertz</b>	69.0 <sup>1</sup>	86.0	1500	4.9	206.3	NC-NST-CCNR2	
<b>50 Hertz</b>	82.0R <sup>1</sup>	103.0	1500	6.5	230.3	NC-NST-	NC
<b>50 Hertz</b>	86.0 <sup>1</sup>	107.0	1500	6.5	219.6	NC-NST-	NC

R – Radiator cooled only.

<sup>1</sup>ABS, BV, DnV, GL, LR, RINA, CCS approved generator set packages available.

Contact local dealer for availability.

	L	H	WE
<b>Open Min.</b>	55.5 in/1409 mm	51.9 in/1318 mm	28.5 in/724 mm
<b>Open Max.</b>	62.6 in/1590 mm	55.3 in/1405 mm	28.5 in/724 mm
<b>Enclosed</b>	68.9 in/1750 mm	39.4 in/1000 mm	47.8 in/1215 mm

### In-line 4, 4-Stroke-Cycle Diesel

<b>Aspiration</b>	NA, T, TA	
<b>Bore x Stroke</b>	4.13 x 5.0 in	105 x 127 mm
<b>Displacement</b>	269 cu in	4.4 liter
<b>Rotation (from flywheel end)</b>	Counterclockwise	
<b>Generator set weight (approx)</b>	1775-2238 lb	805-1015 kg