


Electronic
Control
System



C6.6 ACERT GENERATOR SET

RATINGS AND FUEL CONSUMPTION

Generator Set

	ekW @ .8pf	kVA	rpm	U.S. g/h	g/bkW-hr	EPA - IMO - EU
60 Hertz	113R	141	1800	8.7	223.7	T2C - II -IW
60 Hertz	125	156	1800	8.74	203.1	T2C - II -IW
60 Hertz	138R	173	1800	11.0	231.6	T2C - II -IW
60 Hertz	150	187	1800	11.0	213.1	T2C - II -IW
60 Hertz	158R	198	1800	12.0	220.7	T2C - II -IW
60 Hertz	170	212	1800	12.0	205.1	T2C - II -IW
50 Hertz	93R	116	1500	7.1	221.8	T2C - II -IW
50 Hertz	100	125	1500	7.1	206.3	T2C - II -IW
50 Hertz	118R	148	1500	9.1	224.1	T2C - II -IW
50 Hertz	125	156	1500	9.1	211.5	T2C - II -IW
50 Hertz	136R	170	1500	10.7	228.6	T2C - II -IW
50 Hertz	143	178	1500	10.7	217.4	T2C - II -IW

R – Radiator cooled only.

MCS approved packages available.

Contact local dealer for availability.

	LG	H	WE
min.	75.0-1905.0 mm	37.8 in/961 mm	51.8 in/1315 mm
max.	104.7 in/2660 mm	37.8 in/961 mm	55.7 in/1416 mm

In-line 6, 4-Stroke-Cycle Diesel

Aspiration	TA	
Bore x Stroke	4.13 x 5.0 in	105 x 127 mm
Displacement	402.7 cu in	6.6 liter
Rotation (from flywheel end)	Counterclockwise	
Generator set weight (approx)	2972-3675 lb	1348-1667 kg